

FortiGate® Network Security Platform - *Top Selling Models Matrix

| | FG/FWF-40F | FG/FWF-60F | FG/FWF-80F | FG-100F |
|-------------------------------------------------------------|---------------------------------------|----------------------------|---------------------------------------|-------------------------------------------------------------|
| Firewall Throughput (1518/512/64 byte UDP) | 5 / 5 / 5 Gbps | 10/10/6 Gbps | 10 / 10 / 7 Gbps | 20 / 18 / 10 Gbps |
| IPsec VPN Throughput (512 byte) ¹ | 4.4 Gbps | 6.5 Gbps | 6.5 Gbps | 11.5 Gbps |
| IPS Throughput (Enterprise Mix) ² | 1 Gbps | 1.4 Gbps | 1.4 Gbps | 2.6 Gbps |
| NGFW Throughput (Enterprise Mix) ^{2,4} | 800 Mbps | 1 Gbps | 1 Gbps | 1.6 Gbps |
| Threat Protection Throughput (Ent. Mix) ^{2,5} | 600 Mbps | 700 Mbps | 900 Mbps ⁶ | 1 Gbps |
| Firewall Latency | 2.97 µs | 3.3 µs | 3.23 µs | 4.97µs |
| Concurrent Sessions | 700,000 | 700,000 | 1.5 Million | 1.5 Million |
| New Sessions/Sec | 35,000 | 35,000 | 45,000 | 56,000 |
| Firewall Policies | 5,000 | 5,000 | 5,000 | 10,000 |
| Max G/W to G/W IPSEC Tunnels | 200 | 200 | 200 | 2,000 |
| Max Client to G/W IPSEC Tunnels | 250 | 500 | 2,500 | 16,000 |
| SSL VPN Throughput | 490 Mbps | 900 Mbps | 950 Mbps | 1 Gbps |
| Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode) | 200 | 200 | 200 | 500 |
| SSL Inspection Throughput (IPS, avg. HTTPS) ³ | 310 Mbps | 630 Mbps | 715 Mbps | 1 Gbps |
| Application Control Throughput (HTTP 64K) ² | 990 Mbps | 1.8 Gbps | 1.8 Gbps | 2.2 Gbps |
| Max FortiAPs (Total / Tunnel) | 16 / 8 | 64 / 32 | 96 / 48 | 128 / 64 |
| Max FortiSwitches | 8 | 16 | 16 | 32 |
| Max FortiTokens | 500 | 500 | 500 | 5,000 |
| Virtual Domains (Default/Max) | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 |
| Interfaces | 5x GE RJ45 | 10x GE RJ45 | 8x GE RJ45, 2x Shared Port Pairs | 2x 10 GE SFP+, 18x GE RJ45, 4x Shared Port Pairs, 8x GE SFP |
| Local Storage | — | 128 GB (61F) | 128 GB (81F) | 480 GB (101F) |
| Power Supplies | Single AC PS | Single AC PS | Single AC PS, dual inputs | Dual AC PS |
| Form Factor | Desktop | Desktop | Desktop | 1 RU |
| Variants | WiFi, 3G4G | WiFi, Storage | WiFi, 3G4G, DSL, Bypass, Storage | — |
| | FG-200F | FG-400E | FG-600E | FG-600F |
| Firewall Throughput (1518/512/64 byte UDP) | 27 / 27 / 11 Gbps | 32 / 32 / 24 Gbps | 36 / 36 / 27 Gbps | 139 / 137.5 / 70 Gbps |
| IPsec VPN Throughput (512 byte) ¹ | 13 Gbps | 20 Gbps | 20 Gbps | 55 Gbps |
| IPS Throughput (Enterprise Mix) ² | 5 Gbps | 7.8 Gbps | 10 Gbps | 14 Gbps |
| NGFW Throughput (Enterprise Mix) ^{2,4} | 3.5 Gbps | 6 Gbps | 9.5 Gbps | 11.5 Gbps |
| Threat Protection Throughput (Ent. Mix) ^{2,5} | 3 Gbps | 5 Gbps | 7 Gbps | 10.5 Gbps |
| Firewall Latency | 4.78 µs | 2.14 µs | 1.54 µs | 4.12 µs |
| Concurrent Sessions | 3 Million | 4 Million | 8 Million | 7.8 Million |
| New Sessions/Sec | 280,000 | 450,000 | 450,000 | 550,000 |
| Firewall Policies | 10,000 | 10,000 | 10,000 | 10,000 |
| Max G/W to G/W IPSEC Tunnels | 2,000 | 2,000 | 2,000 | 2,000 |
| Max Client to G/W IPSEC Tunnels | 16,000 | 50,000 | 50,000 | 50,000 |
| SSL VPN Throughput | 2 Gbps | 4.5 Gbps | 7 Gbps | 4.3 Gbps |
| Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode) | 500 | 5,000 | 10,000 | 10,000 |
| SSL Inspection Throughput (IPS, avg. HTTPS) ³ | 4 Gbps | 4.8 Gbps | 8 Gbps | 9 Gbps |
| Application Control Throughput (HTTP 64K) ² | 13 Gbps | 12 Gbps | 15 Gbps | 32 Gbps |
| Max FortiAPs (Total / Tunnel) | 256 / 128 | 512 / 256 | 1,024 / 512 | 1024 / 512 |
| Max FortiSwitches | 64 | 72 | 96 | 96 |
| Max FortiTokens | 5,000 | 5,000 | 5,000 | 5,000 |
| Virtual Domains (Default/Max) | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 |
| Interfaces | 4x 10 GE SFP+, 18x GE RJ45, 8x GE SFP | 18x GE RJ45, 16x GE SFP | 2x 10 GE SFP+, 10x GE RJ45, 8x GE SFP | 4x 25G SFP28, 4x 10GE SFP+, 18 x GE RJ45 |
| Local Storage | 480 GB (201F) | 480 GB (401E) | 480 GB (601E) | 480 GB (601F) |
| Power Supplies | Dual AC PS | Single AC PS, opt. Dual PS | Single AC PS, opt. Dual PS | Dual AC PS |
| Form Factor | 1 RU | 1 RU | 1 RU | 1 RU |
| Variants | — | — | — | — |

FortiGate® Network Security Platform - *Top Selling Models Matrix

| | FG-1100E | FG-1800F | FG-2200E | FG-2600F |
|-------------------------------------------------------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|--------------------------------------------------------|-------------------------------------------------------------------------------------|
| Firewall Throughput (1518/512/64 byte UDP) | 80 / 80 / 45 Gbps | 198 / 197 / 140 Gbps | 158 / 155 / 100 Gbps | 198 / 196 / 120 Gbps |
| IPsec VPN Throughput (512 byte) ¹ | 48 Gbps | 55 Gbps | 98 Gbps | 55 Gbps |
| IPS Throughput (Enterprise Mix) ² | 12.5 Gbps | 17 Gbps | 21 Gbps | 24 Gbps |
| NGFW Throughput (Enterprise Mix) ^{2,4} | 9.8 Gbps | 11 Gbps | 13.5 Gbps | 19 Gbps |
| Threat Protection Throughput (Ent. Mix) ^{2,5} | 7.1 Gbps | 9.1 Gbps | 11 Gbps | 17 Gbps |
| Firewall Latency | 2.76 µs | 3.22 µs | 3.09 µs | 3.41 µs |
| Concurrent Sessions | 8 Million | 12 Million / 40 Million ⁷ | 24 Million | 24 Million / 40 Million ⁷ |
| New Sessions/Sec | 500,000 | 750,000 / 2 Million ⁷ | 500,000 | 1 Million / 2 Million ⁷ |
| Firewall Policies | 100,000 | 100,000 | 100,000 | 100,000 |
| Max G/W to G/W IPSEC Tunnels | 20,000 | 20,000 | 20,000 | 20,000 |
| Max Client to G/W IPSEC Tunnels | 100,000 | 100,000 | 100,000 | 100,000 |
| SSL VPN Throughput | 8.4 Gbps | 11 Gbps | 10 Gbps | 16 Gbps |
| Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode) | 10,000 | 10,000 | 30,000 | 30,000 |
| SSL Inspection Throughput (IPS, avg. HTTPS) ³ | 10 Gbps | 12 Gbps | 17 Gbps | 20 Gbps |
| Application Control Throughput (HTTP 64K) ² | 26 Gbps | 34 Gbps | 52 Gbps | 64 Gbps |
| Max FortiAPs (Total, Tunnel) | 4,096 / 2,048 | 4,096 / 2,048 | 4,096 / 2,048 | 4,096 / 2,048 |
| Max FortiSwitches | 196 | 196 | 196 | 196 |
| Max FortiTokens | 20,000 | 20,000 | 20,000 | 20,000 |
| Virtual Domains (Default/Max) | 10 / 250 | 10 / 250 | 10 / 500 | 10 / 500 |
| Interfaces | 2x 40GE QSFP+, 4x 25GE SFP28, 4x 10GE SFP+, 8x GE SFP, 18x GE RJ45 | 4x 40 GE QSFP+, 12x 25 GE SFP28, 2x10 GE SFP+, 8x GE SFP, 18x GE RJ45 | 4x 40GE QSFP+, 20x 25GE SFP28, 14x GE RJ45 | 4x 100GE QSFP28/40GE QSFP+, 16x 25GE SFP28, 16x 10GE RJ45, 2x 10GE SFP+, 2x GE RJ45 |
| Local Storage | 960 GB (1101E) | 2 TB (1801F) | 2 TB (2201E) | 2 TB (2601F) |
| Power Supplies | Dual PS | Dual PS | Dual PS | Dual PS |
| Form Factor | 2 RU | 2 RU | 2 RU | 2 RU |
| Variants | DC | DC | — | DC |
| | FG-3000F | FG-3300E | FG-3400E | FG-3500F |
| Firewall Throughput (1518/512/64 byte UDP) | 397 / 389 / 221 Gbps | 160 / 158 / 100 Gbps | 240 / 238 / 150 Gbps | 595 / 590 / 420 Gbps |
| IPsec VPN Throughput (512 byte) ¹ | 105 Gbps | 98 Gbps | 140 Gbps | 165 Gbps |
| IPS Throughput (Enterprise Mix) ² | 36 Gbps | 27 Gbps | 44 Gbps | 72 Gbps |
| NGFW Throughput (Enterprise Mix) ^{2,4} | 34 Gbps | 23 Gbps | 34 Gbps | 65 Gbps |
| Threat Protection Throughput (Ent. Mix) ^{2,5} | 33 Gbps | 17 Gbps | 25 Gbps | 63 Gbps |
| Firewall Latency | 3.92 µs | 3.17 µs | 3.33 µs | 2.98 µs |
| Concurrent Sessions | 70 Million / 230 Million ⁷ | 50 Million | 50 Million | 140 Million / 348 Million ⁷ |
| New Sessions/Sec | 870 000 / 3 Million ⁷ | 700,000 | 850,000 | 1 Million / 5 Million ⁷ |
| Firewall Policies | 200,000 | 200,000 | 200,000 | 200,000 |
| Max G/W to G/W IPSEC Tunnels | 40,000 | 40,000 | 40,000 | 40,000 |
| Max Client to G/W IPSEC Tunnels | 200,000 | 200,000 | 200,000 | 200,000 |
| SSL VPN Throughput | 11 Gbps | 10 Gbps | 11 Gbps | 16 Gbps |
| Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode) | 30,000 | 30,000 | 30,000 | 30,000 |
| SSL Inspection Throughput (IPS, avg. HTTPS) ³ | 29 Gbps | 21 Gbps | 30 Gbps | 63 Gbps |
| Application Control Throughput (HTTP 64K) ² | 115 Gbps | 70 Gbps | 86 Gbps | 135 Gbps |
| Max FortiAPs (Total, Tunnel) | 4,096 / 2,048 | 4,096 / 2,048 | 4,096 / 2,048 | 4,096 / 2,048 |
| Max FortiSwitches | 300 | 300 | 300 | 300 |
| Max FortiTokens | 20,000 | 20,000 | 20,000 | 20,000 |
| Virtual Domains (Default/Max) | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 |
| Interfaces | 6x 100GE QSFP28/40GE QSFP+, 16x 25GE SFP28, 18x 10GE RJ45, 2x GE RJ45 | 4x 40GE QSFP+, 16x 25GE SFP28, 4x 10GE RJ45, 14x GE RJ45 | 4x 100GE QSFP28/40GE QSFP+, 24x 25GE SFP28, 2x GE RJ45 | 6x 100GE QSFP28/40GE QSFP+, 32x 25GE SFP28, 2x GE RJ45 |
| Local Storage | 2 TB (3001F) | 2 TB (3301E) | 4 TB (3401E) | 4 TB (3501F) |
| Power Supplies | Dual PS | Dual PS | Dual PS | Dual PS |
| Form Factor | 2 RU | 2 RU | 2 RU | 2 RU |
| Variants | — | — | DC | — |

* Featured Top selling models, for complete FortiGate offerings please visit www.fortinet.com. FortiGate virtual appliances are also available. All performance values are "up to" and vary depending on system configuration.



FortiGate® Network Security Platform - *Top Selling Models Matrix

| | FG-3600E | FG-3700F | FG-3960E | FG-3980E | FG-4200F |
|-------------------------------------------------------------|---------------------------------------------------------|----------------------------------------------------------------------|----------------------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|
| Firewall Throughput (1518/512/64 byte UDP) | 240 / 240 / 150 Gbps | 589 / 589 / 420 Gbps | 620 / 610 / 370 Gbps | 1.05 Tbps / 1.05 Tbps / 680 Gbps | 800 / 788 / 400 Gbps |
| IPsec VPN Throughput (512 byte) ¹ | 140 Gbps | 160 Gbps | 280 Gbps | 400 Gbps | 210 Gbps |
| IPS Throughput (Enterprise Mix) ² | 55 Gbps | 86 Gbps | 30 Gbps | 32 Gbps | 52 Gbps |
| NGFW Throughput (Enterprise Mix) ^{2,4} | 40 Gbps | 80 Gbps | 22 Gbps | 28 Gbps | 47 Gbps |
| Threat Protection Throughput (Ent. Mix) ^{2,5} | 30 Gbps | 75 Gbps | 13.5 Gbps | 20 Gbps | 45 Gbps ⁶ |
| Firewall Latency | 3.27µs | 3.56 µs / 1.45 µs ⁸ | 3 µs | 3 µs | 3.02 µs |
| Concurrent Sessions | 50 Million | 140 Million | 160 Million | 160 Million | 210 Million / 450 Million ⁷ |
| New Sessions/Sec | 950,000 | 930,000 | 720,000 | 800,000 | 1 Million / 7 Million ⁷ |
| Firewall Policies | 200,000 | 200,000 | 200,000 | 200,000 | 200,000 |
| Max G/W to G/W IPSEC Tunnels | 40,000 | 40,000 | 40,000 | 40,000 | 40,000 |
| Max Client to G/W IPSEC Tunnels | 200,000 | 200,000 | 200,000 | 200,000 | 200,000 |
| SSL VPN Throughput | 12 Gbps | 16 Gbps | 9 Gbps | 9.5 Gbps | 16 Gbps |
| Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode) | 30,000 | 30,000 | 30,000 | 30,000 | 30,000 |
| SSL Inspection Throughput (IPS, avg. HTTPS) ³ | 34 Gbps | 55 Gbps | 23 Gbps | 26 Gbps | 50 Gbps |
| Application Control Throughput (HTTP 64K) ² | 95 Gbps | 190 Gbps | 40 Gbps | 55 Gbps | 135 Gbps |
| Max FortiAPs (Total, Tunnel) | 4,096 / 2,048 | 4,096 / 2,048 | 8,192 / 4,096 | 8,192 / 4,096 | 8,192 / 4,096 |
| Max FortiSwitches | 300 | 300 | 300 | 300 | 300 |
| Max FortiTokens | 20,000 | 20,000 | 20,000 | 20,000 | 20,000 |
| Virtual Domains (Default/Max) | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 |
| Interfaces | 6x 100GE QSFP28/40GE QSFP+, 32x 25GE SFP28, 2x GE RJ45 | 4x 400GE QSFP-DD, 4x ULL 25GE SFP28, 20x 50GE SFP56, 2x 10GE RJ45 | 6x 100GE QSFP28/40GE QSFP+, 16x 10GE SFP+, 2x GE RJ45 | 10x 100GE QSFP28/40GE QSFP+, 16x 10GE SFP+, 2x GE RJ45 | 8x 100GE QSFP28/40GE QSFP+, 18x 25GE SFP28, 2x GE RJ45 |
| Local Storage | 4 TB (3601E) | 4 TB (3701E) | — | — | 4 TB (4201F) |
| Power Supplies | Dual PS | Dual PS | 3 PS | 3 PS | Dual PS |
| Form Factor | 2 RU | 2 RU | 5 RU | 5 RU | 3 RU |
| Variants | DC | — | DC | DC | DC |
| | FG-4400F | FG-6300F | FG-6500F | FG-7060E | FG-7121F/-2 |
| Firewall Throughput (1518/512/64 byte UDP) | 1.15 / 1.14 / 0.50 Tbps | 239 / 238 / 135 Gbps | 239 / 238 / 135 Gbps | 630 / 630 / 340 Gbps | 1.89 / 1.88 / 1.129 Tbps |
| IPsec VPN Throughput (512 byte) ¹ | 310 Gbps | 96 Gbps | 160 Gbps | 100 Gbps | 630 Gbps |
| IPS Throughput (Enterprise Mix) ² | 94 Gbps | 110 Gbps | 170 Gbps | 200 Gbps | 675 Gbps |
| NGFW Throughput (Enterprise Mix) ^{2,4} | 82 Gbps | 90 Gbps | 150 Gbps | 120 Gbps | 550 Gbps |
| Threat Protection Throughput (Ent. Mix) ^{2,5} | 75 Gbps ⁶ | 60 Gbps | 100 Gbps | 96 Gbps | 520 Gbps |
| Firewall Latency | 2.98 µs | 5 µs | 5 µs | 7 µs | 7.5 µs |
| Concurrent Sessions | 210 Million / 700 Million ⁷ | 120 Million | 200 Million | 320 Million | 1 Billion |
| New Sessions/Sec | 1 Million / 10 Million ⁷ | 2 Million | 3 Million | 1.8 Million | 9 Million |
| Firewall Policies | 200,000 | 200,000 | 200,000 | 200,000 | 200,000 |
| Max G/W to G/W IPSEC Tunnels | 40,000 | 16,000 | 16,000 | 16,000 | 40,000 |
| Max Client to G/W IPSEC Tunnels | 200,000 | 90,000 | 90,000 | 64,000 | 260,000 |
| SSL VPN Throughput | 16 Gbps | 9 Gbps | 9 Gbps | 15 Gbps | 13.7 Gbps |
| Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode) | 30,000 | 30,000 | 30,000 | 48,000 | 30,000 |
| SSL Inspection Throughput (IPS, avg. HTTPS) ³ | 86 Gbps | 66 Gbps | 110 Gbps | 79.9 Gbps | 540 Gbps |
| Application Control Throughput (HTTP 64K) ² | 140 Gbps | 150 Gbps | 220 Gbps | 160 Gbps | 1.5 Tbps |
| Max FortiAPs (Total, Tunnel) | 8,192 / 4,096 | — | — | — | — |
| Max FortiSwitches | 300 | 256 | 256 | 256 | 300 |
| Max FortiTokens | 20,000 | 20,000 | 20,000 | 20,000 | 20,000 |
| Virtual Domains (Default/Max) | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 |
| Interfaces | 12x 100GE QSFP28/40GE QSFP+, 20x 25GE SFP28, 2x GE RJ45 | 4x 100GE QSFP28/40GE QSFP+, 24x 25GE SFP28, 3x 10GE SFP+, 2x GE RJ45 | 4x 100GE QSFP28/40GE QSFP+, 24x 25GE SFP28, 3x 10GE SFP+, 2x GE RJ45 | Varied | Varied |
| Local Storage | 4 TB (4401F) | 2 TB NVMe (6301F) | 2 TB NVMe (6501F) | — | 4x 4 TB SSD |
| Power Supplies | 4 PS | 3 PS | 3 PS | 4+2 PS | 8 PS |
| Form Factor | 4 RU | 3 RU | 3 RU | 8 RU | 16 RU |
| Variants | DC | DC | DC | DC | DC |

1. IPsec VPN performance test uses AES256-SHA256.

2. IPS, Application Control, NGFW and Threat Protection are measured with Logging enabled.

3. SSL Inspection performance values use an average of HTTPS sessions of different cipher suites.

4. NGFW performance is measured with Firewall, IPS and Application Control enabled, Enterprise Mix traffic.

5. Threat Protection performance is measured with Firewall, IPS, Application Control, (6.URL Filtering) and Malware Protection enabled, Enterprise Mix traffic.

7. Requires Hyperscale license

8. With Ultra-Low Latency ports



FortiManager™ Centralized Management Platform

| | FMG-200G | FMG-300F | FMG-400G | FMG-1000F | FMG-2000E | FMG-3000G | FMG-3700G | FMG-VM-BASE to FMG-VM-UL-UG |
|-------------------------|------------|-----------------------|-----------------------|--------------------------|--------------------------|---------------------------|---------------------------------|-----------------------------|
| Devices/VDOMs (Maximum) | 30 | 100 | 150 | 1,000 | 1,200 | 4,000+ | 10,000+ | 10 to Unlimited |
| Sustained Log Rates | 50 | 50 | 50 | 50 | 50 | 150 | 150 | Hardware dependent |
| GB/Day | 2 | 2 | 2 | 2 | 2 | 10 | 10 | 1-50 |
| Total Interfaces | 4x GE RJ45 | 4x GE RJ45, 2x GE SFP | 4x GE RJ45, 2x GE SFP | 2x GE RJ45, 2x 10GE SFP+ | 4x GE RJ45, 2x 10GE SFP+ | 2x GE RJ45, 2x 25GE SFP28 | 2x 10GE RJ45, 2x 25GE SFP28 | 1 / 4 (vNIC Min / Max) |
| Storage Capacity | 2x 4 TB | 4x 4 TB | 8x 4 TB | 8x 4 TB | 12x 3 TB | 16x 4 TB | 60x 4TB HDD + 6x 3.2TB NVMe SSD | 80 GB / 16 TB (Min / Max) |

FortiAnalyzer™ Centralized Logging and Reporting Solution

| | FAZ-150G | FAZ-300G | FAZ-800G | FAZ-1000F | FAZ-3000G | FAZ-3500G | FAZ-3700G | FAZ-VM-BASE to FAZ-VM-GB2000 |
|-------------------------------------|------------|------------|-----------------------|--------------------------|---------------------------|---------------------------|---------------------------------|------------------------------|
| GB Logs/Day | 25 | 100 | 200 | 660 | 3,000 | 5,000 | 8,300 | 1 to +2,000 |
| Analytic Sustained Rate (logs/sec) | 500 | 2,000 | 4,000 | 20,000 | 42,000 | 60,000 | 100,000 | — |
| Collector Sustained Rate (logs/sec) | 750 | 3,000 | 6,000 | 30,000 | 60,000 | 90,000 | 150,000 | — |
| Total Interfaces | 2x GE RJ45 | 4x GE RJ45 | 4x GE RJ45, 2x GE SFP | 2x GE RJ45, 2x 10GE SFP+ | 2x GE RJ45, 2x 25GE SFP28 | 2x GE RJ45, 2x 25GE SFP28 | 2x 10GE RJ45, 2x 25GE SFP28 | 1 / 4 (vNIC Min / Max) |
| Storage Capacity | 2x 2 TB | 2x 4 TB | 4x 4 TB | 8x 4 TB | 16x 4 TB | 24x 4 TB | 60x 4TB HDD + 6x 3.2TB NVMe SSD | 500 GB to +100 TB |

FortiSIEM™ Unified Event Correlation and Risk Management Solution

| | FSM-500G "COLLECTOR" | FSM-2000G "SUPERVISOR" | FSM-3500G "SUPERVISOR" |
|-------------------------------------|----------------------|------------------------|------------------------|
| All-in-One License Capacity | N/A | Up to 500 | Up to 2,000 |
| EPS Capacity (all features enabled) | 5,000 | Up to 20,000 | Up to 40,000 |

FortiAuthenticator™ User Identity Management Server

| | FAC-300F | FAC-800F | FAC-3000F | FAC-VM BASE to FAC-VM-10000-UG |
|--------------------------------------|-------------|--------------------|--------------------|--------------------------------|
| Max Local + Remote Users/ User Group | 1,500 / 150 | 8,000 / 800 | 40,000 / 240,000 | 100 / 10 to +10,000 / 1,000 |
| Max NAS Devices | 500 | 2,666 | 80,000 | 33 to +33,333 |
| Max FortiTokens | 3,000 | 16,000 | 480,000 | 200 to +20,000 |
| Interfaces | 4x GE RJ45 | 4x GE RJ45, 2x SFP | 4x GE RJ45, 2x SFP | 1 - 4 vNICs |
| Storage Capacity | 2 | 2x 2 TB | 2x 2 TB | 60 GB to 16 TB |

FortiAP™ Wireless Access Point

| | FortiAP Series | FortiAP U-Series |
|------------|----------------------------------|------------------------------------------------------|
| Management | FortiGate-Managed, Cloud-Managed | FortiGate-Managed, Cloud-Managed, Controller-Managed |
| Security | Via FortiGate | Via FortiGate |

* Frequency selection and power may be restricted to abide by regional regulatory compliance laws. For Complete selection of FortiAPs, including remote and outdoor devices, please refer to Fortinet Wireless Solution Matrix

FortiSwitch™ Secured Access Switch

| | 100 Series | 200 Series | 400 Series | 500 Series | 1000 Series | 3000 Series |
|--------------------------|--------------|-------------|-------------|--------------|----------------|-------------|
| Main Port Speed | 1 Gbps | 1 Gbps | 1 Gbps | 1 Gbps | 10/40 Gbps | 40/100 Gbps |
| Main Port Count Options | 8, 24, 48 | 24, 48 | 24, 48 | 24, 48 | 24, 48 | 32 |
| Uplink Port Speed | 1 or 10 Gbps | 1 Gbps | 10 Gbps | 10 Gbps | 40 or 100 Gbps | n/a |
| Redundant Power Supplies | — | Some Models | Some Models | Optional RSU | • | • |
| PoE Options | • | • | • | • | — | — |

For Complete selection of FortiSwitches, please refer to <http://www.fortinet.com/products/fortiswitch>



FortiNAC™ Network Access Control Solution

| | FNC-CA-500C | FNC-CA-600C | FNC-CA-700C | FNC-M-550C |
|--------------------|-------------------------------------------|-------------------------------------------------|-------------------------------------------------------|--------------------------------------------------|
| Type | Mid-range Control and Application Server | High Performance Control and Application Server | Ultra High Performance Control and Application Server | Centralized Management Appliance |
| Target Environment | Small Environments | Medium Environments | Large Environments with few Persistent Agents | Multi-site environments with multiple appliances |
| Capacity | Manages up to 1,000 ports in the network* | Manages up to 7,500 ports in the network* | Manages up to 15,000 ports in the network* | Unlimited |

Virtual appliances are also available, please refer to www.fortinet.com for more information

FortiSandbox™ Advanced Threat Prevention System

| | PAAS FORTISANDBOX CLOUD | FSA-VM | FSA-500F | FSA-1000F/-DC | FSA-2000E | FSA-3000F |
|-----------------------------------------------------------|-------------------------|-------------|----------------|-----------------|-----------------|-----------------|
| Effective Sandboxing Throughput ¹ (Files/Hour) | 20 - 4,000 | 100 - 4,000 | 500 | 1,000 | 1,400 | 3,700 |
| Number of Users ² | 10 - 2,000 | 50 - 2,000 | 500 | 700 | 1,000 | 6,000 |
| Number of VMs | up to 200 | up to 8 | 2 + 4 Optional | 2 + 12 Optional | 4 + 20 Optional | 8 + 64 Optional |

1. Tested based on files with 80% documents and 20% executables. Includes both Static and Dynamic analysis with pre-filtering enabled.
2. Based on a ratio of 20 files per users on a 10-hour period.

FortiClient™ Advanced Endpoint Security

| | Windows | MAC OS X | Linux | Android | iOS | Chromebook |
|-------------------------------------------------------|---------|----------|--------------|---------|--------------|------------|
| Zero Trust Security (ZTNA) Options | ☑ | ☑ | ☑ | — | — | Partial |
| Next Generation Endpoint Security (EPP / APT) Options | ☑ | ☑ | ☑ | — | — | — |
| Cloud Based Endpoint Security (SASE) Options | ☑ | ☑ | ☑ | — | — | — |
| Security Fabric Components | ☑ | ☑ | Partial | Partial | Partial | Partial |
| VPN Client | ☑ | ☑ | SSL VPN only | ☑ | SSL VPN only | — |

FortiMail™ Messaging Security Server

| | FML-200F | FML-400F | FML-900F | FML-2000F | FML-3000F | FML-3200E |
|--------------------------------------|----------|----------|--------------------|---------------------|---------------------|---------------------|
| Email Routing* (Msg/Hr) | 50,000 | 250,000 | 800,000 | 1.6 Mil | 3.5 Mil | 3.4 Mil |
| Performance Enterprise ATP* (Msg/Hr) | 30,000 | 150,000 | 400,000 | 800,000 | 2.1 Mil | 2.0 Mil |
| Email Domains | 20 | 100 | 800 | 1,000 | 2,000 | 2,000 |
| Server Mode Mailboxes | 150 | 400 | 1,500 | 2,000 | 3,000 | 3,000 |
| Storage Capacity | 1× 1 TB | 2× 1 TB | 2× 2 TB (8 TB Max) | 2× 2 TB (12 TB Max) | 2× 2 TB (20 TB Max) | 2× 2 TB (20 TB Max) |

* Measured based on 100KB message size, no queuing.
Virtual appliances are also available, please refer to www.fortinet.com for more information

FortiWeb™ Web Application Firewall

| | FWB-100E | FWB-400E | FWB-600E | FWB-1000E | FWB-2000F | FWB-3000F | FWB-4000F |
|-------------------|------------|-------------------------|------------------------------------|------------------------------------------------|--------------------------------------------|---------------------------------------------------|------------------------------------------------------------------------|
| Throughput (HTTP) | 50 Mbps | 250 Mbps | 750 Mbps | 1.3 Gbps | 5 Gbps | 10 Gbps | 70 Gbps |
| Total Interfaces | 4x GE RJ45 | 4x GE RJ45 4x GE SFP | 2 (+2 bypass) x GE RJ45, 4x GE SFP | 2 (+4 bypass) GE RJ45, 4x SFP GE, 2x 10GE SFP+ | 4x 10GE SFP+, 4x GE RJ45 Bypass, 4x GE SFP | 10x 10GE SFP+ (incl. 2 Bypass), 8x GE RJ45 Bypass | 2x 40GE QSFP Bypass, 10x 10GE SFP+ (incl. 2 Bypass), 8x GE RJ45 Bypass |

Virtual appliances are also available, please refer to www.fortinet.com for more information



Virtual Appliance Support Matrix

| | VMWare vSphere | Citrix Xen Server | Xen | KVM | Microsoft Hyper-V | Nutanix AHV | Amazon AWS | Microsoft Azure | Oracle OPC/OCI | Google GCP | Alibaba Aliyun |
|-----------------------|----------------|-------------------|-----|-----|-------------------|-------------|------------|-----------------|----------------|------------|----------------|
| FortiGate-VM * | • | • | • | • | • | • | • / # | • / # | • / # | • / # | • / # |
| FortiManager-VM | • | • | • | • | • | • | • / # | • | • | • | • |
| FortiAnalyzer-VM | • | • | • | • | • | • | • / # | • | • | • | • |
| FortiWeb-VM | • | • | • | • | • | • | • / # | • / # | • | • | • |
| FortiWeb Manager-VM | • | | | | | | • | | | | |
| FortiMail-VM | • | • | | • | • | • | • / # | • / # | | • | |
| FortiAuthenticator-VM | • | | • | • | • | | • | • | • | | |
| FortiADC-VM | • | • | • | • | • | • | • / # | • / # | • / # | • / # | |
| FortiVoice-VM | • | • | | • | • | | • | • | | | |
| FortiRecorder-VM | • | • | | • | • | | # | | | | |
| FortiSandbox-VM | • | | | • | • | • | • / # | # | | | |
| FortiSIEM-VM | • | | | • | • | • | • | • | | | • |
| FortiProxy-VM | • | | | • | | | | | | | |

*Available as FortiGate-VMX solution for VMware NSX environment, AzureStack and RackSpace (PAYG) # on-demand

List of Other Products

FortiADC Application Delivery Controller
FortiAI Virtual Security Analyst™
FortiCASB Cloud Access Security Broker
FortiCarrier CGN Gateway
FortiCWP Cloud Security Analytics
FortiDDoS DDoS Mitigator
FortiDeceptor Deception-based Solution
FortiEDR EDR Solution

FortiExtender 3G/4G WAN Extender
FortiHypervisor Hybrid Virtual Appliance
FortiInsight UEBA Solution
FortiIsolator Browser Isolation Platform
FortiMonitor NPMD, DEM and IM Systems
FortiProxy Secure Web Gateway
FortiRecorder Network Video Security
FortiSIEM SIEM with UEBA Solution

FortiSOAR SOAR Solution
FortiTester Network Tester
FortiToken 2 Factor Authentication Token
FortiVoice Secure VoIP Solution
FortiWLC Wireless Controller
FortiWLM Wireless Manager
FortiXDR Extended Detection and Response



www.fortinet.com

Copyright © 2022 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.

Fortinet is committed to driving progress and sustainability for all through cybersecurity, with respect for human rights and ethical business practices, making possible a digital world you can always trust. You represent and warrant to Fortinet that you will not use Fortinet's products and services to engage in, or support in any way, violations or abuses of human rights, including those involving censorship, surveillance, detention, or excessive use of force. Users of Fortinet products are required to comply with the Fortinet EULA (<https://www.fortinet.com/content/dam/fortinet/assets/legal/EULA.pdf>) and report any suspected violations of the EULA via the procedures outlined in the Fortinet Whistleblower Policy (https://secure.ethicspoint.com/domain/media/en/gui/19775/Whistleblower_Policy.pdf).